



ARIHANT CHEMICAL CORPORATION

24/5, Krishna kunj bldg, behind arora cinema, opp.sahakari bhandar, sewari wadala road, Matunga (C.R), Mumbai-400019.

MOBILE NO :- 9820142066/9029042066 E-MAIL :- accounts@arihantchemcorp.com / nilesh.arihant@yahoo.com

TEL NO :- 022-24148378 OR 022-24146390.

WAX 32 AF

PE WAX

Wax 32 AF include straight chain, linear polyethylene and their modified products, can be used in wood lacquers, coating, ink and powder coating. There are performance improved for scratch resistance & rub resistance.

TYPICAL PROPERTIES:

PROPERTIES	UNITS	WAX 32 AF
Appearance	-	White Powder
D(50)-50% Particles Below	μ	12 – 15
Melting Point	$^{\circ}\text{C}$	115 – 125
Moisture	%	0.0 – 0.5
Brook Field Viscosity At 140 $^{\circ}\text{C}$	Centipoises	150 - 170
Bulk Density (Loose)	gm/ltr	250 – 300

KEY BENEFITS:

- Outstanding transparency
- Scratch resistance
- Rub resistance
- Gloss Retention
- Easy to disperse

APPLICATION:

- Gravure Printing Ink
- Offset Printing Ink
- Flexo Printing Ink